

Technical Notes

APPLE RUST PREVENTIVE 5M - 8004

Date - 11/10/2016-001

Category - Clear Coat

Description

1k low viscous quick drying rust preventive coating based on natural binder.



Recommended Use

We recommended this product to protect machining parts from flush rust.
For example shafting, bearing, housing surface, etc.

Technical Data

Color	Yellow/Red
Finish	Satin
Volume Solid	11%
Recommended DFT	3 to 5μ
Theoretical Coverage	22-3 6.66 sq. mt/ltr.
Flash Point	Above 10° C
Drying Time	Surface dry - 5 to 10 min tack free -30 min
Mixing Ratio	NA
Over Coatability	NA

Surface Preparation

Apply direct on all Job.

Application Details

THINNER	NA
VOLUME OF THINNER	NA

Application Method

By Brush or padding.

Additional Information

For further information, please go through MSDS of the product.

Notes

Check points before painting

1. Brush equipment should be cleaned with NC thinner.
2. Shelf life indicated is minimum of this product in sealed condition and it is subjected to re inspection thereafter.

Health & Safety

This is a solvent-based paint so the required preventions should be taken to avoid inhalation of spray mist or vapor as well as contact between the wet paint and exposed skin or eyes.

Packing Size

1 ltrs And 5 ltrs

Limitation Of Liability

To the best of our knowledge, the technical data in our literature are true and accurate at the data of issuance but are subject to change without prior notice. We guarantee our product to conform specification contained herein. We make no other warranty or guarantee of any kind, express or implied including merchantability and fitness of particular purpose.